

# Motion Sensors

## A-TS1 - Admore Time Switch

Brand: Admore



## A-MS4 - Admore Recessed Ceiling Motion Sensor

Brand: Admore

Voltage: 220-240V/AC

Power Frequency: 50/60Hz

Color: White

Casting Material: PVC

IP Rating: IP20

Rated Load (Florescent): 1200W

Rated Load (LED): 600W

Time Delay: Min. 10sec ± 3sec

Photosensitive settings: < 3 - 2000Lux (adjustable)

Detaction Range: 360°

Detection Distance: 6m max

Working Temperature: -20~+40°C

Working Humidity: <93%RH

Installation Type: Recessed

Detection Speed: 0.6~1.5m/s

Guarantee: 5 Years



## A-MS3 - Admore Motion Sensor Switch

Brand: Admore

Voltage: 220-240V/AC

Power Frequency: 50/60Hz

Color: White

Casting Material: PVC

IP Rating: IP20

Rated Load (Florescent): 2000W

Rated Load (LED): 1000W

Time Delay: Min. 10sec ± 3sec

Photosensitive settings: < 3 - 2000Lux (adjustable)

Detaction Range: 360°

Detection Distance: 30m max

Working Temperature: -20~+40°C

Working Humidity: <93%RH

Installation Type: Surface

Detection Speed: 0.6~1.5m/s

Guarantee: 5 Years



## A-MS2 - Admore Motion Sensor Switch

Brand: Admore

Voltage: 220-240V/AC

Power Frequency: 50/60Hz

Color: White

Casting Material: PVC  
IP Rating: IP20  
Rated Load (Florescent): 2000W  
Rated Load (LED): 1000W  
Time Delay: Min. 10sec  $\pm$  3sec  
Photosensitive settings: < 3 - 2000Lux (adjustable)  
Detaction Range: 360°  
Detection Distance: 3 - 20m max (adjustable)  
Working Temperature: -20~+40°C  
Working Humidity: <93%RH  
Installation Type: Surface  
Detection Speed: 0.6~1.5m/s  
Guarantee: 5 Years



اضواء الجزيرة للكهربائيات ذ.م.م.

ADWA AL-JAZEERA

Electricals L.L.C.

